






QUICK REFERENCE TABLE

MICRO BLOWERS

機種選択表

シリーズ名 Series name	TF037C		TF037E	TF037F	TF029B
	取付金具付き With Mounting Bracket	取付金具無し Without Mounting Bracket			
					
定格電圧 Rated Voltage	10~30 VDC	10~30 VDC	10~30 VDC	10~30 VDC	DC 12~27 V
定格電源電流 Rated Power Supply Current	0.9 A Max.	0.9 A Max.	0.9 A Max.	0.9 A Max.	0.62 A Max.
定格消費電力 Rated Power Consumption	21.6 W Max.	21.6 W Max.	21.6 W Max.	21.6 W Max.	14.9 W Max.
動作回転数範囲 Rated Rotation Speed	6,000~45,000 rpm	6,000~45,000 rpm	6,000~45,000 rpm	6,000~45,000 rpm	10,000~50,000 rpm
最低流量 Minimum Flowrate	5 L/min	5 L/min	5 L/min	5 L/min	10 L/min
動作時周囲気圧 Operating Ambient Pressure	770~1,060 hPa	770~1,060 hPa	770~1,060 hPa	770~1,060 hPa	900~1,060 hPa
最大入力コイル電流 Maximum input coil current	3.0 A Max.	3.0 A Max.	3.0 A Max.	3.0 A Max.	2.0 A Max.
使用温度範囲 Operating temperature	-10~60°C	-10~60°C	-10~60°C	-10~60°C	0~50°C
騒音 Acoustic Audible Noise	65.0 dB(A) Max.	65.0 dB(A) Max.	65.0 dB(A) Max.	65.0 dB(A) Max.	65.0 dB(A) Max.
取付金具 Mounting Bracket	付 With	無 Without	付 With	無 Without	無 Without
質量 Weight	約 94 g Approx. 94 g	約 90 g Approx. 90 g	約 165 g Approx. 165 g	約 72 g Approx. 72 g	約 55 g Approx. 55 g
ドライバセット販売 Driver Set Available	有 Yes	無 No	無 No	有 Yes	有 Yes
使用材料 Material	使用樹脂材料に UL94 V0 を採用 Resin in full compliance with UL94 V0			使用樹脂材料は FDA 準拠材を採用 Resin in full compliance with FDA standards	
掲載ページ Page	412 ~ 416		417 ~ 420	421 ~ 424	425 ~ 428